

## **MINORE®**

### **Compact and economical**



## **MINORE®**

The MINORE® is a small circulatory cooler available in 300W, 350W and 500W versions. A cooling unit cools the circulating water and/or antifreeze mixture in a small container, from where it is supplied to the cooling unit by a circulation pump.

The container is easily accessible and can be filled from under the hinged cover on the top of the unit.

This type of unit is available in the same size of casing up to 600 W and 3.0 bars pump pressure and can be supplied as an air or water cooled version. Other temperature ranges are available.

### **Application examples**

- Rotary evaporators
- Distillation devices
- Soxhlet extractions
- Water baths

### **Features and advantages**

- 100% water savings in tap water
- No sewage costs for waste water

- Cooling water temperature, pressure and flow can be regulated
- Constant water quality, no limescale, no algae
- Minimum space requirement on every laboratory table
- Compact 5 litre tank
- Almost noiseless
- Temperature display in O-LED capacitive touch pad controller
- Lockable castors
- Acoustic and text description alarm Display
- Ambient temperature up to 32°C
- Available with higher pump pressure and many different options and accessories
- Power regulation by microprocessor controlled heating, this means high temperature stability of water pre-run temperature (0.1 K/°C)

## Technical Data

Technical Data	MINORE® 0	MINORE® I	MINORE® II
Temperature range	16-22° C	16-22° C	16-22° C
Cooling power @ 20°C	300 watt	350 watt	500 watt
Pump capacity max.	28 l/min.	28 l/min.	28 l/min.
Feed pressure max.	0.4 bar	0.4 bar	0.4 bar
Connections	Quick lock with 9 mm hose sleeves	Quick lock with 9 mm hose sleeves	Quick lock with 9 mm hose sleeves
Dimensions W x D x H	360 x 470 x 590 mm	360 x 470 x 590 mm	360 x 470 x 590 mm
Current	230 V/50 Hz/1 PH	230 V/50 Hz/1 PH	230 V/50 Hz/1 PH
Power consumption	220 Watt max.	270 Watt max.	340 Watt max.
Weight	25 kg	37 kg	38 kg
Refrigerant	R 134 a	R 134 a	R 134 a
Part no. Air cooled	0-RB400	I-RB400	II-RB400
Part no. Water cooled	0-WG-RB400	I-WG-RB400	II-WG-RB400